

**Rapporto/Report No. K 2064 2021 B4**

Decreto 7 Novembre 2017, n. 186  
Certificazione ambientale del generatore di  
calore

Types:  
**PF 721**

Produttore / Manufacturer:  
**JOTUL FRANCE SAS**



This accreditation is valid only for the listed standards as stated in the accreditation annex of D-PL-11120-04-00

**This report may only be published and forwarded to third parties in its complete, unabridged form. The publication or dissemination of extracts, summaries, appraisals or any other adaptation and alterations, in particular for advertising purposes, is only permissible with the prior written permission of TÜV Rheinland.  
Publication of page 2 is permitted.**

**The test results presented in this report refer solely to the test object stated as described on page 2. The report does not represent a general statement about the serial production of the test object and gives not an authorization for use of a TÜV Rheinland test- / certification mark.**

**Decreto 7 Novembre 2017, n. 186**  
**Certificazione ambientale del generatore di calore**

Produttore / <i>Manufacturer:</i>	<b>JOTUL FRANCE SAS</b> 3, chemin du jubin F-69574 Dardilly Cedex
Tipo / <i>Type:</i>	<b>PF 721</b>
Potenza termica nominale / <i>Nominal heat output:</i>	7,0 kW
Tipologia prodotti / <i>Product types:</i>	Stufe a pellets di legna / Wood pellet stoves
Norma di riferimento / <i>Reference standard:</i>	EN 14785:2006
Ente Notificato CPR/ <i>Notified body acc. CPR</i>	NB 2456
Rapporto di Prova di riferimento / <i>Reference test report:</i>	K20642017Z1
Combustibile di prova / <i>Test fuel:</i>	Pellet di legna / <i>Wood pellet</i>

Cologne, 29.10.2021  
432 / pom

Assessor:



Dipl.-Ing. A. Pomp

TÜV Rheinland Energy GmbH  
Test Centre for Energy Appliances  
NB 2456 (CPR)  
DIN EN ISO/IEC 17025:2005  
accreditation: D-PL-11120-04-00

Report released after review:

Dipl.-Ing. M. Reibold

<b>Prestazioni del generatore di calore</b> <b>Performances of the heating appliance</b> <b>Classi di prestazione / Performance class</b>				
<b>PF 721</b>				
<b>PP<sup>(1)</sup> mg/Nm<sup>3</sup></b>	<b>9,4 (5*)</b>			
<b>COT<sup>(1)</sup> mg/Nm<sup>3</sup></b>	<b>1,2 (5*)</b>			
<b>NOx<sup>(1)</sup> mg/Nm<sup>3</sup></b>	<b>131 (4*)</b>			
<b>CO<sup>(2)</sup> mg/Nm<sup>3</sup></b>	<b>26 (5*)</b>			
<b>η<sup>(2)</sup> %</b>	<b>89,0 (5*)</b>			
<b>Result / Class</b>	<b>4 stelle / 4 stars</b>			
<p><sup>(1)</sup> Determinato applicando il metodo di misura della UNI CEN/TS 15883  <i>Determined applying the measurement method of the UNI CEN/TS 15883</i></p> <p><sup>(2)</sup> Determinato secondo la EN 14785:2006  <i>Determined according to EN 14785:2006</i></p> <p>Nota: tutti i valori di concentrazione calcolati al 13% di O<sub>2</sub> in condizioni normali (273 K, 1013 mbar, gas secco)  <i>Note: all the concentration values are calculated at 13% of O<sub>2</sub> in normal conditions (273 K, 1013 mbar, dry gas)</i></p>				
<b><u>Limit Values</u></b>				
	<b>5 stelle</b>	<b>4 stelle</b>	<b>3 stelle</b>	<b>2 stelle</b>
<b>PP<sup>(1)</sup> mg/Nm<sup>3</sup></b>	15	20	30	50
<b>COT<sup>(1)</sup> mg/Nm<sup>3</sup></b>	10	35	50	80
<b>NOx<sup>(1)</sup> mg/Nm<sup>3</sup></b>	100	160	200	200
<b>CO<sup>(2)</sup> mg/Nm<sup>3</sup></b>	250	250	364	500
<b>η<sup>(2)</sup> %</b>	88	87	85	85