

Declaration of Performance (DoP)

No. F3TD -CPR-130913	
Product Type:	Roomheaters fired by solid fuel
Type, batch or serial number:	Jøtul F 3 TD
Intended use of the product:	Roomheater burning solid fuel without water supply
Name and Address of the manufacturer:	Jøtul AS
	Postboks 1411, 1602 Fredrikstad, Norway
	Tel.: +47 69 35 90 00
	E-mail: post@jotul.no
AVCP: System(s) of assessment and verification of constancy op performance (AVCP) of the construction product as set out in	System 3
CPR, Annex V Notified body:	SP Technical Research Institute of Sweden
NB-No:	0402
Test report no: Declared performance:	P5 03789-H
<u> </u>	EN 12240-2001 /A2-2004 /AC-2007
Harmonized technical specification	EN 13240:2001/A2:2004/AC:2007
Essential characteristics	Performance
Fire safety	
Reaction to fire	A1
Distance to combustible materials Pick of burning fuel falling out	Minimum distances, in mm
	Rear = 600
	Sides = 700
	Corner = 600
	Front = NPD
	See also the installation instructions
Risk of burning fuel falling out Emission of combustion products	No CO [0,30 %]
Emission of compassion products	[0,50 /0]
Surface temperature	Pass
Electrical safety	-
Cleanability	Pass
Maximum water operating pressure	- T[220°C]
Flue gas temperature at nominal heat output Mechanical resistance (to carry a chimney/flue)	T [330°C] NPD
Thermal output	NI D
Normal heat output	7 kW
Room heating output	- kW
Water heating output	-*kW
Energy efficiency	η [79%]

Declaration:

The performance of the product in conformity with the declared performance.

This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed on behalf of the manufacturer:

Tom J. Berglind

R&D Manager

(Name and function)

Fredrikstad, August 23rd 2013

(Place and date of issue)

(Signature)